

LYRA 20 LED SR/T2




Part number	06109390
Lampholder:	LED
Light Source:	LED
Wattage:	70 W
Finish:	GR-RAL7035 / Grey RAL7035 / Matt
Insulation class:	II
Degree of protection:	IP66
IK-J-xxIP:	IK08 7J xx5
CRI:	70
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	ROAD REFLECTOR
Lightsource lumen output:	8608 lm
Luminaire lumen output:	7012 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-40°
Ta MAX luminaire:	40°
ULR:	0%
IPEA* (Street Lighting):	A++
IPEA* (Area Lighting):	A3+
IPEA* (Cycle/Pedestrian Lighting):	A+
IPEA* (Green Areas):	A+
IPEA* (Historical Areas):	A5+
Luminous Intensity Class:	G*3




Description

- Series of street luminaires, comprising:
- Pole clamp in die-cast aluminium painted with polyester powder for post top installation $\varnothing 60$, $\varnothing 76$ or on arms $\varnothing 42$ - $\varnothing 60$
 - Technopolymer housing
 - Diffuser with integrated louvre in UV, heat stabilised, transparent technopolymer
 - High-transparency polycarbonate lenses for best light transmission
 - Anti-aging silicone gasket with high resiliency
 - Switch splitter automatically disconnects the power supply when the cable cover is opened
 - Aluminium heat dissipation system
 - Light beam obtained by the combination of multiple LED modules
 - Stainless steel external screws
 - Stainless steel retaining clips
 - Galvanised steel gear tray bracket
 - The "SECURE LIGHT DISTRIBUTION" system guarantees uniform light distribution even in the remote case of LED failures
 - Compliant with the UNI 10819 Standard and with the Italian regional laws on light pollution
 - On request, versions with dimmable ballast available
 - Replaceable LED module
 - Versions with automatic power reduction available

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

LYRA 20 LED



14152017

Wall angled bracket in hot dipped
galvanized steel, cataphoresis and
finished polyester