



WHERE THE BASE (ROAD BASE) HAS BEEN USED AS A TEMPORARY RUNNING SURFACE DURING THE CONTRACT IT SHALL BE THOROUGHLY CLEANED AND POWER WASHED AS NECESSARY. AFTER DRYING AND IMMEDIATELY BEFORE THE BINDER COURSE IS LAID A TACK COAT OF BITUMEN EMULSION CLASS A1-40 OR K1-40 TO BS434 SHALL BE APPLIED AT A RATE OF 0.35-0.55 LITRES/SQ METER. ALL RADIUS KERBS WITH A RADIUS OF 12m OR LESS SHALL BE FORMED WITH PROPRIETARY RADIUS KERBS.

- [illegible]

[illegible]

	SITE BOUNDARY
	MAJOR CONTOUR
	MINOR CONTOUR
	FLOOD ROUTING ARROW
	POTENTIAL PONDING WHEN DRAINAGE IS BLOCKED

8.07.2026	MINOR CHANGES	NA	AE	3
8.03.2026	UPDATED TO SUIT NEW LAYOUT	NA	AE	2
6.03.2026	FIRST ISSUE	NA	AE	1
Date	Revisions	Drawn	Checked	Rev

Dwg Status	SCHEMATIC
------------	-----------

© 2015 Pearson Education, Inc. or its affiliate(s). All rights reserved.

D W D

NORTH EAST
0191 3565432

VIDEO CLIP

CONSULTING ENGINEERS

WWW.RWO.GROUP
INFO@RWO.GROUP

VISTRY GROUP

VICTORY GROUP

Project	
---------	--

SHAW LANE
CATERINGCARLTON

Title	Author	Year	Journal	Volume	Page
...	...	...	...	...	...

FLOOD ROUTING PLAN[illegible]

DO NOT SCALE	Scale @ A0: 1:500	Drawn NA	Checked AE	Date 03.03.2026
--------------	-------------------	----------	------------	-----------------

Jsb No	24307	Dwg No	D206	Rev	03
--------	-------	--------	------	-----	----