

Appendix 3

Geotechnical Test Results (PSL20/1337)

Infiltration Test Results (TP4 and TP5)



LABORATORY REPORT



4043

Contract Number: PSL20/1337

Report Date: 06 March 2020
Client's Reference: 44856
Client Name: Eastwood & Partners
St Andrews House
23 Kingfield Road
Sheffield
S11 9AS

For the attention of: Josephine Hicks

Contract Title: Lower Eastfield Farm, Thurgoland, Sheffield
Date Received: 3/3/2020
Date Commenced: 3/3/2020
Date Completed: 6/3/2020

Notes: Opinions and Interpretations are outside the UKAS Accreditation

A copy of the Laboratory Schedule of accredited tests as issued by UKAS is attached to this report. This certificate is issued in accordance with the accreditation requirements of the United Kingdom Accreditation Service. The results reported herein relate only to the material supplied to the laboratory. This certificate shall not be reproduced other than in full, without the prior written approval of the laboratory.

Checked and Approved Signatories:


R Gunson
(Director)

A Watkins
(Director)

R Berriman
(Quality Manager)

S Royle
(Laboratory Manager)

S Eyre
(Senior Technician)



L Knight
(Senior Technician)

5 – 7 Hexthorpe Road, Hexthorpe,
Doncaster DN4 0AR
tel: +44 (0)844 815 6641
fax: +44 (0)844 815 6642
e-mail: rgunson@prosoils.co.uk
awatkins@prosoils.co.uk

Page 1 of

SUMMARY OF LABORATORY SOIL DESCRIPTIONS

Hole Number	Sample Number	Sample Type	Top Depth m	Base Depth m	Description of Sample
TP02		D	2.60	3.00	Brown highly weathered MUDSTONE.

 4043		Lower Eastfield Farm, Thurgoland, Sheffield	Contract No:
			PSL20/1337
			Client Ref:
			44856


SUMMARY OF SOIL CLASSIFICATION TESTS

(BS1377 : PART 2 : 1990)

Hole Number	Sample Number	Sample Type	Top Depth m	Base Depth m	Moisture Content % <small>Clause 3.2</small>	Linear Shrinkage % <small>Clause 6.5</small>	Particle Density Mg/m ³ <small>Clause 8.2</small>	Liquid Limit % <small>Clause 4.3/4</small>	Plastic Limit % <small>Clause 5.3</small>	Plasticity Index % <small>Clause 5.4</small>	Passing .425mm %	Remarks
TP02		D	2.60	3.00	14			41	24	17	60	Intermediate plasticity CI.

SYMBOLS : NP : Non Plastic


* : Liquid Limit and Plastic Limit Wet Sieved.



Lower Eastfield Farm, Thurgoland, Sheffield

Contract No:
PSL20/1337
Client Ref:
44856

PLASTICITY CHART FOR CASAGRANDE CLASSIFICATION.



4043

PSL
Professional Soils Laboratory

Lower Eastfield Farm, Thurgoland, Sheffield

Contract No:

PSL20/1337

Client Ref:

44856

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB


Test No. TP4 - Test 1

Test Pit Dimensions

Length = **2200** mm Plan area = **1.43** m²
 Width = **650** mm
 Depth = **1300** mm (Total depth)

Approximate time to discharge water into the hole: **30** Seconds
 Depth to water after completion of pumping: **800** mm

Time (min)	Depth (mm)
0	800
0.5	1000
1	1100
1.5	1200
2	1300
2.5	1300



Test Pit Log

Depth (m)	Description
0-0.2	TOPSOIL
0.2-1.5	COBBLES with some sandy clayey gravel

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB

Test No. TP4 - Test 1

Soil Infiltration Rate in Accordance with BR365

$$f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$$

Where: V_{p75-25} is the effective storage volume of water in the trial pit between 75% and 25% effective depth;

a_{p50} is the internal surface area of the trial pit up to 50% effective depth and including the base area

t_{p75-25} is the time for the water level to fall from 75% to 25% effective depth

Initial parameters

Depth to water = **800 mm** Average water depth: **250 mm**
 Start time = **0 min** Change in water depth: **500 mm**

Final parameters

Depth to water = **1300 mm** Time interval: **2.5 min**
 End time = **3 min**

Effective Storage Volume of Water in the Trial Pit = **0.715 m³**
 75% Effective Depth = **925 mm** from ground level
 25% Effective Depth = **1175 mm** from ground level
 Time at 75% Effective Depth = **0 minutes**
 Time at 25% Effective Depth = **1.4 minutes**

V_{p75-25} = **0.36 m³**

a_{p50} = **2.86 m²**

t_{p75-25} = **66 sec**

f = **1.9E-03 m/sec**

Average Soakaway Rate = **4.8E-03 m³/sec**
 Average soakaway area = **2.86 m²** (sides + base)

BR365 Soil Infiltration Rate = 1.9E-03 m/sec
Average Infiltration Rate = 1.7E-03 m/sec

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB


Test No. TP4 - Test 2

Test Pit Dimensions

Length = **2200** mm Plan area = **1.43** m²
 Width = **650** mm
 Depth = **1300** mm (Total depth)

Approximate time to discharge water into the hole: **30** Seconds
 Depth to water after completion of pumping: **700** mm

Time (min)	Depth (mm)
0	700
0.5	900
1	1100
1.5	1200
2	1300
2.5	1300



Test Pit Log

Depth (m)	Description
0-0.2	TOPSOIL
0.2-1.5	COBBLES with some sandy clayey gravel

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB

Test No. TP4 - Test 2

Soil Infiltration Rate in Accordance with BR365

$$f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$$

Where: V_{p75-25} is the effective storage volume of water in the trial pit between 75% and 25% effective depth;

a_{p50} is the internal surface area of the trial pit up to 50% effective depth and including the base area

t_{p75-25} is the time for the water level to fall from 75% to 25% effective depth

Initial parameters

Depth to water = **700** mm Average water depth: **300** mm
 Start time = **0** min Change in water depth: **600** mm

Final parameters

Depth to water = **1300** mm Time interval: **2.5** min
 End time = **3** min

Effective Storage Volume of Water in the Trial Pit = **0.858** m³
 75% Effective Depth = **850** mm from ground level
 25% Effective Depth = **1150** mm from ground level
 Time at 75% Effective Depth = **0** minutes
 Time at 25% Effective Depth = **1.15** minutes

V_{p75-25} = **0.43** m³

a_{p50} = **3.14** m²

t_{p75-25} = **45** sec

f = **3.0E-03** m/sec

Average Soakaway Rate = **5.7E-03** m³/sec
 Average soakaway area = **3.14** m² (sides + base)

BR365 Soil Infiltration Rate = 3.0E-03 m/sec
Average Infiltration Rate = 1.8E-03 m/sec

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB


Test No. TP4 - Test 3

Test Pit Dimensions

Length = **2200** mm Plan area = **1.43** m²
Width = **650** mm
Depth = **1300** mm (Total depth)

Approximate time to discharge water into the hole: **30** Seconds
Depth to water after completion of pumping: **700** mm

Time (min)	Depth (mm)
0	700
0.5	900
1	1000
1.5	1100
2	1200
2.5	1200
3	1300
3.5	1300



Test Pit Log

Depth (m)	Description
0-0.2	TOPSOIL
0.2-1.5	COBBLES with some sandy clayey gravel

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB

Test No. TP4 - Test 3

Soil Infiltration Rate in Accordance with BR365

$$f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$$

Where: V_{p75-25} is the effective storage volume of water in the trial pit between 75% and 25% effective depth;

a_{p50} is the internal surface area of the trial pit up to 50% effective depth and including the base area

t_{p75-25} is the time for the water level to fall from 75% to 25% effective depth

Initial parameters

Depth to water = **700** mm Average water depth: **300** mm
 Start time = **0** min Change in water depth: **600** mm

Final parameters

Depth to water = **1300** mm Time interval: **3.5** min
 End time = **4** min

Effective Storage Volume of Water in the Trial Pit = **0.858** m³
 75% Effective Depth = **850** mm from ground level
 25% Effective Depth = **1150** mm from ground level
 Time at 75% Effective Depth = **0** minutes
 Time at 25% Effective Depth = **1.65** minutes

V_{p75-25} = **0.43** m³
 a_{p50} = **3.14** m²
 t_{p75-25} = **74** sec
 f = **1.9E-03** m/sec

Average Soakaway Rate = **4.1E-03** m³/sec
 Average soakaway area = **3.14** m² (sides + base)

BR365 Soil Infiltration Rate = 1.9E-03 m/sec
Average Infiltration Rate = 1.3E-03 m/sec

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB

Test No. TP5 - Test 1

Soil Infiltration Rate in Accordance with BR365

$$f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$$

- Where:
- V_{p75-25} is the effective storage volume of water in the trial pit between 75% and 25% effective depth;
 - a_{p50} is the internal surface area of the trial pit up to 50% effective depth and including the base area
 - t_{p75-25} is the time for the water level to fall from 75% to 25% effective depth

Initial parameters

Depth to water = **1400** mm Average water depth: **450** mm
 Start time = **0** min Change in water depth: **700** mm

Final parameters

Depth to water = **2100** mm Time interval: **7** min
 End time = **7** min

Effective Storage Volume of Water in the Trial Pit = **1.904** m³
 75% Effective Depth = **1600** mm from ground level
 25% Effective Depth = **2000** mm from ground level
 Time at 75% Effective Depth = **1** minutes
 Time at 25% Effective Depth = **5** minutes

V_{p75-25} = **0.95** m³

a_{p50} = **5.66** m²

t_{p75-25} = **240** sec

f = **7.0E-04** m/sec

Average Soakaway Rate = **4.0E-03** m³/sec
 Average soakaway area = **6.07** m² (sides + base)

BR365 Soil Infiltration Rate = 7.0E-04 m/sec
Average Infiltration Rate = 6.5E-04 m/sec

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB


Test No. TP5 - Test 2

Test Pit Dimensions

Length = **3400 mm** Plan area = **2.38 m²**
 Width = **700 mm**
 Depth = **1900 mm (Total depth)**

Approximate time to discharge water into the hole: **30 Seconds**
 Depth to water after completion of pumping: **1300 mm**

Time (min)	Depth (mm)
0	1300
1	1400
2	1500
3	1600
4	1700
5	1700
6	1700
7	1800
9	1900



Test Pit Log

Depth (m)	Description
0-0.1	Reworked TOPSOIL
0.1-0.5	MADE GROUND - Granular
0.5-1.1	MADE GROUND - Cohesive
1.1-1.7	Clayey GRAVEL with low cobble content
1.7-2.2	COBBLES with some sandy clayey gravel

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB

Test No. TP5 - Test 2

Soil Infiltration Rate in Accordance with BR365

$$f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$$

- Where:
- V_{p75-25} is the effective storage volume of water in the trial pit between 75% and 25% effective depth;
 - a_{p50} is the internal surface area of the trial pit up to 50% effective depth and including the base area
 - t_{p75-25} is the time for the water level to fall from 75% to 25% effective depth

Initial parameters

Depth to water = **1400** mm Average water depth: **250** mm
 Start time = **0** min Change in water depth: **500** mm

Final parameters

Depth to water = **1900** mm Time interval: **9** min
 End time = **9** min

Effective Storage Volume of Water in the Trial Pit = **1.428** m³
 75% Effective Depth = **1450** mm from ground level
 25% Effective Depth = **1750** mm from ground level
 Time at 75% Effective Depth = **2** minutes
 Time at 25% Effective Depth = **6.5** minutes

V_{p75-25} = **0.71** m³

a_{p50} = **4.84** m²

t_{p75-25} = **300** sec

f = **4.9E-04** m/sec

Average Soakaway Rate = **2.2E-03** m³/sec
 Average soakaway area = **4.43** m² (sides + base)

BR365 Soil Infiltration Rate = 4.9E-04 m/sec
Average Infiltration Rate = 5.0E-04 m/sec

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB


Test No. TP5 - Test 3

Test Pit Dimensions

Length = **3400** mm Plan area = **2.38** m²
 Width = **700** mm
 Depth = **1900** mm (Total depth)

Approximate time to discharge water into the hole: **30** Seconds
 Depth to water after completion of pumping: **1400** mm

Time (min)	Depth (mm)
0	1400
1	1450
2	1500
3	1600
4	1700
5	1800
6	1900
7	1900
9	1900



Test Pit Log

Depth (m)	Description
0-0.1	Reworked TOPSOIL
0.1-0.5	MADE GROUND - Granular
0.5-1.1	MADE GROUND - Cohesive
1.1-1.7	Clayey GRAVEL with low cobble content
1.7-2.2	COBBLES with some sandy clayey gravel

PROJECT:	Lower Eastfield Farm, Thurgoland	Job No. 44856	Date 18/02/2020
SUBJECT:	Infiltration Test Results and Calculation of Infiltration Rates	Prepared JH	Checked GCB

Test No. TP5 - Test 3

Soil Infiltration Rate in Accordance with BR365

$$f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}$$

Where: V_{p75-25} is the effective storage volume of water in the trial pit between 75% and 25% effective depth;

a_{p50} is the internal surface area of the trial pit up to 50% effective depth and including the base area

t_{p75-25} is the time for the water level to fall from 75% to 25% effective depth

Initial parameters

Depth to water = **1400** mm Average water depth: **250** mm

Start time = **0** min

Change in water depth: **500** mm

Final parameters

Depth to water = **1900** mm Time interval: **9** min

End time = **9** min

Effective Storage Volume of Water in the Trial Pit = **1.19** m³
 75% Effective Depth = **1525** mm from ground level
 25% Effective Depth = **1775** mm from ground level
 Time at 75% Effective Depth = **2** minutes
 Time at 25% Effective Depth = **4.6** minutes

V_{p75-25} = **0.60** m³

a_{p50} = **4.43** m²

t_{p75-25} = **138** sec

f = **9.7E-04** m/sec

Average Soakaway Rate = **2.2E-03** m³/sec

Average soakaway area = **4.43** m² (sides + base)

BR365 Soil Infiltration Rate = 9.7E-04 m/sec

Average Infiltration Rate = 5.0E-04 m/sec