

DO NOT SCALE

NOTES

GENERAL NOTES

- a. THE TOPOGRAPHICAL SURVEY IS BASED ON INFORMATION PRODUCED FROM FIRST POINT SURVEYS DRAWING No. 5679-01. THE INFORMATION USED IN PREPARATION OF THIS AND ALL OTHER JPG DESIGNS AND DRAWINGS IS NOT WARRANTED. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO VERIFY ALL SURVEY INFORMATION PROVIDED AND REPORT ANY ANOMALIES TO JPG.

DESIGN NOTES

- ALL DESIGN AND WORKS TO COMPLY WITH CURRENT VERSION OF THE FOLLOWING DOCUMENTS:
 - DESIGN MANUAL FOR ROADS AND BRIDGES (DMRB)
 - SPECIFICATION FOR HIGHWAY WORKS (SHW)
 - BARNSELY COUNCIL DESIGN GUIDE AND SPECIFICATION.
- UNCONTROLLED PEDESTRIAN CROSSINGS CONSTRUCTION AND ARRANGEMENT TO BE IN ACCORDANCE WITH BARNSELY COUNCIL FOOTPATH GRADIENT AT TACTILE PAVING TO BE A MAXIMUM OF 1:12.
- EXISTING FENCES, VERGES/SHUBBERY, FOOTWAY COBBLES, FOUNDATIONS, WALLS, STREET LIGHTING COLUMNS AND OTHER PHYSICAL FEATURES TO BE REMOVED WITHIN THE AREA OF WORKS.
- ALL FENCING SHALL BE TAKEN UP AND REMOVED FROM SITE AND SHALL BE CARRIED OUT IN ACCORDANCE WITH THE SPECIFICATION FOR HIGHWAY WORKS CLAUSE 201.6 AND SUITABLY DISPOSED.
- BOUNDARY FENCING SHALL BE PROVIDED SUBJECT TO AGREEMENT WITH BARNSELY COUNCIL AND LANDSCAPING REQUIREMENTS.
- ALL IRONWORK WITHIN EXTENT OF WORKS TO BE LOWERED / RAISED AS REQUIRED.
- STATUTORY UNDERTAKERS NOTE: CONTRACTOR TO LOCATE ALL STATUTORY SERVICES ON SITE. STATUTORY UNDERTAKERS EQUIPMENT TO BE PROTECTED/LOWERED OR ARRANGE DIVERSION AS NECESSARY IN ACCORDANCE WITH THE REQUIREMENTS OF THE NEW ROADS AND STREET WORKS ACT 1991. EVIDENCE MUST BE PROVIDED TO THE LOCAL AUTHORITY THAT STATUTORY UNDERTAKERS INFORMATION IN THE LOCATION OF THE WORKS AND CONFIRM DETAILS OF ANY DIVERSIONARY WORKS REQUIRED.
- ALL PROPOSED ROAD MARKINGS TO BE IN ACCORDANCE WITH THE FOLLOWING:
 - TRAFFIC SIGNS REGULATIONS AND GENERAL DIRECTIONS (TSRGD)
 - TRAFFIC SIGNS MANUALS CHAPTER 5 - ROAD MARKINGS.
- ANY OVERBREAK IN CARRIAGEWAY SHALL BE BACKFILLED WITH CONCRETE GRADE S14 TO THE UNDERSIDE OF SURFACE COURSE. A MINIMUM 300mm WIDE STRIP OF EXISTING SURFACE COURSE MUST BE PLACED TO A DEPTH OF 50mm AND RELAID ALONG THE FACE OF THE NEW KERBS. THE EXPOSED SURFACES MUST BE TREATED WITH A BITUMEN TACK COAT BEFORE THE NEW SURFACE IS LAID.
- KERB RADIUS WHERE LESS THAN 12m SHALL BE TRUE RADIUS KERBS
- FOR LONGSECTION DETAILS AND LEVELS PLEASE REFER TO JPG DRAWING 4652-2-JPG-SW-00-DR-D-1605
- FOR HIGHWAY STANDARD DETAILS PLEASE REFER TO JPG DRAWING 4652-2-JPG-SW-00-DR-D-1608
- FOR TYPICAL SECTION DETAILS PLEASE REFER TO JPG DRAWING 4652-2-JPG-SW-00-DR-D-1609

KEY

- SITE BOUNDARY
- EXTENT OF EARTHWORKS BATTER TO EXISTING LEVELS
- EXISTING WATERCOURSE/ LAND DRAIN

NOTE:
SIGNAGE AND LIGHTING TO BE DESIGNED BY BMBC

P04	PLOT 3 ENTRY ARM UPDATED, ACO BARRIER PROVIDED TO OUTER ROUNDABOUT	13.04.20	RMR
P03	ADDITIONAL ANNOTATIONS AND BUILT UP REFERENCES ADDED. TYPICAL SECTION MOVED TO HIGHWAY STANDARD DETAILS.	12.03.20	LSG
P02	ADDITIONAL DETAILED ADDED	27.02.20	GB
P01	FIRST ISSUE.	17.01.20	LSG
REV	DESCRIPTION	DATE	BY

Project
ROCKINGHAM 2&3
HOYLAND

Drawing Title
SECTION 278
GENERAL ARRANGEMENT

INFORMATION ISSUE

Architect
THE HARRIS PARTNERSHIP



JPG Project Ref	Scale at A1	Date	Checked	Drawn
4652-2	1:500	17.01.20	GB	LSG
4652-2 - JPG - SW - 00 - DR - D - 1601			S2	P04