



GENERAL SAFETY NOTES:

- WHERE THE BASE (ROAD BASE) HAS BEEN USED AS A TEMPORARY RUNNING SURFACE DURING THE CONTRACT IT SHALL BE THOROUGHLY CLEANED AND POWER WASHED AS NECESSARY AFTER DRYING AND IMMEDIATELY BEFORE THE FINISH COURSE IS Laid A 100mm COAT OF BRUSHED EMULSION CLASS A14 OR A14-2 SHALL BE APPLIED AT A RATE OF 0.15-0.25 LITRES/SQ METRE
- ALL SLOPES EXCEEDING A RATIO OF 1 IN 10 SHALL BE FORMED WITH PROPERLY RADIUS DROPS

HEALTH & SAFETY:

- CONTRACTOR SHOULD BE AWARE OF GENERAL CONSTRUCTION RISKS TO PREVENT SLIPS, TRIPS AND FALLS AND TAKE NECESSARY PRECAUTIONS WITHOUT SPECIAL INSTRUCTION
- CONTRACTOR TO PROVIDE FRENCH SUPPORTS AT APPROPRIATE AND ENSURE THAT PLANT REMAINS A SAFE DISTANCE FROM TRENCHES PRIOR TO INSTALLING DRAINAGE
- THE TIME THAT EXCAVATING AND GRAD ON SITE SHOULD BE KEPT TO A MINIMUM AND ALL TRENCHES SHOULD BE SURROUNDED BY A BARRIER
- CONNECTIONS TO EXISTING SERVICES TO BE MADE BY APPROVED CONTRACTOR ONLY
- CONTRACTOR TO MAKE OPERATIVES AWARE OF ASSOCIATED DANGERS TO HEALTH SUCH AS LIFTED LOADS, UNSTABLE SURFACES AND RECOMMENDED PRECAUTIONS, ADEQUATE WELFARE FACILITIES AND PROTECTIVE CLOTHING TO BE PROVIDED AS REQUIRED
- UNPROTECTED MANHOLES MUST BE COVERED WITH LOAD BEARING MATERIALS AND SURROUNDED WITH BARRIER

Pipes & Cables:

- CONTRACTOR TO OBTAIN ALL SERVICE RECORDS PRIOR TO WORKS COMMENCING
- SERVICE RECORDS TO BE REFERRED TO PRIOR TO WORK COMMENCING. CONTRACTOR TO PROCEED WITH CAUTION AND SERVICES TO BE LOCATED BY HAND DIG AND PROTECTED ACCORDINGLY
- CONTRACTOR TO ENSURE BULKHEAD MEASURES ARE TAKEN TO KEEP PLANT AND PEOPLE A SAFE DISTANCE FROM STEEP SLOPES DURING THE WORKS
- CONTRACTOR TO ENSURE THAT PROCEEDURES ARE IN PLACE TO KEEP PEOPLE A SAFE DISTANCE FROM WORKING PLANT WHERE NECESSARY
- CONTRACTOR TO REFER TO BRIDGING INSPECTION REPORT FOR CONSUMMATION TESTS AND TO PROVIDE ADEQUATE WELFARE FACILITIES AND PROTECTIVE CLOTHING AS REQUIRED

KEY

- NON-ADOPTED PRIVATE FOOTPATH AND CYCLEWAY
20mm OF AC DENSE SURF 100/750 DES TO BS EN 12183-1 AND PD 6691
100mm OF AC DENSE SURF 100/750 DES TO BS EN 12183-1 AND PD 6691
100mm TYPE 1 SUBBASE REFER TO NHC CHAPTER 02 TABLE 4 FOR FURTHER DETAILS
- PRIVATE DRIVE
25mm AC DENSE SURF 100/750 DES TO BS EN 12183-1 AND PD 6691
100mm AC DENSE SURF 100/750 DES TO BS EN 12183-1 AND PD 6691
100mm TYPE 1 SUBBASE REFER TO NHC CHAPTER 02 TABLE 4 FOR FURTHER DETAILS
- PRIVATE SHARED DRIVE
25mm AC DENSE SURF 100/750 DES TO BS EN 12183-1 AND PD 6691
100mm AC DENSE SURF 100/750 DES TO BS EN 12183-1 AND PD 6691
100mm TYPE 1 SUBBASE REFER TO NHC CHAPTER 02 TABLE 4 FOR FURTHER DETAILS
- PILOT PATH
PAVING SLABS TO ARCHITECTS SPECIFICATION
20mm OF 1.1 CEMENT SAND MORTAR
100mm OF TYPE 1 SUBBASE
- PRIVATE TARMAC FOOTPATH
25mm AC DENSE SURF 100/750
100mm AC DENSE SURF 100/750
100mm TYPE 1 SUBBASE
- H20/25/55 HALF BATTERED KERB (25mm FACE)
- H20/25/55 DROPPED BULLDOSE KERB (3-4mm FACE)
- H20/25/55 TRANSITION KERB (HALF BATTERED TO BULLDOSE)
- ELEVATION FLAT TOP EDGING KERB

07.09.2020	PILOT PYS SIDE PATH CHANGED TO TARMAC	NA	AE	4
01.09.2020	UPDATED TO SUIT CLIENT COMMENTS	SR	AE	3
20.08.2020	UPDATED TO SUIT NEW LAYOUT	SR	AE	2
01.08.2020	FIRST ISSUE	JC	JP	1

Date	Revisions	Drawn	Checked	Rev
Dwg Status	TENDER			

NORTH EAST
(BY 200402)

YORKSHIRE
015 535 2950

Client
VISTRY GROUP

Project
SHAW LANE
CARLTON

Title
SURFACING AND KERBING LAYOUT
OVERALL PLAN

DO NOT SCALE | Scale @ A3: 1:500 | Drawn: JC | Checked: JP | Date: 22.06.2020

Job No: 24307 | Dwg No: D500 | Rev: 4

RWO

CONSULTING ENGINEERS

WWW.RWOGROUP.COM
INFO@RWOGROUP.COM