

3E Consulting Engineers Ltd				Page 2																																																																
4 Calder Close Wakefield WF4 3BA																																																																				
Date 12/06/2017 11:31 File Full SW Model.MDX		Designed by john.mitchell Checked by																																																																		
Micro Drainage		Network 2017.1.1																																																																		
<u>Area Summary for Storm</u> <table><thead><tr><th>Pipe Number</th><th>PIMP Type</th><th>PIMP Name</th><th>PIMP (%)</th><th>Gross Area (ha)</th><th>Imp. Area (ha)</th><th>Pipe Total (ha)</th></tr></thead><tbody><tr><td>1.000</td><td>-</td><td>-</td><td>100</td><td>0.014</td><td>0.014</td><td>0.014</td></tr><tr><td>1.001</td><td>-</td><td>-</td><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>1.002</td><td>-</td><td>-</td><td>100</td><td>0.009</td><td>0.009</td><td>0.009</td></tr><tr><td>1.003</td><td>-</td><td>-</td><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>2.000</td><td>-</td><td>-</td><td>100</td><td>0.034</td><td>0.034</td><td>0.034</td></tr><tr><td>1.004</td><td>-</td><td>-</td><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td colspan="4"></td><td>Total</td><td>Total</td><td>Total</td></tr><tr><td colspan="4"></td><td>0.057</td><td>0.057</td><td>0.057</td></tr></tbody></table>						Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)	1.000	-	-	100	0.014	0.014	0.014	1.001	-	-	100	0.000	0.000	0.000	1.002	-	-	100	0.009	0.009	0.009	1.003	-	-	100	0.000	0.000	0.000	2.000	-	-	100	0.034	0.034	0.034	1.004	-	-	100	0.000	0.000	0.000					Total	Total	Total					0.057	0.057	0.057
Pipe Number	PIMP Type	PIMP Name	PIMP (%)	Gross Area (ha)	Imp. Area (ha)	Pipe Total (ha)																																																														
1.000	-	-	100	0.014	0.014	0.014																																																														
1.001	-	-	100	0.000	0.000	0.000																																																														
1.002	-	-	100	0.009	0.009	0.009																																																														
1.003	-	-	100	0.000	0.000	0.000																																																														
2.000	-	-	100	0.034	0.034	0.034																																																														
1.004	-	-	100	0.000	0.000	0.000																																																														
				Total	Total	Total																																																														
				0.057	0.057	0.057																																																														
<u>Free Flowing Outfall Details for Storm</u> <table><thead><tr><th>Outfall Pipe Number</th><th>Outfall Name</th><th>C. Level (m)</th><th>I. Level (m)</th><th>Min I. Level (m)</th><th>D, L (mm)</th><th>W (mm)</th></tr></thead><tbody><tr><td>1.004</td><td></td><td>187.500</td><td>185.672</td><td>0.000</td><td>0</td><td>0</td></tr></tbody></table>						Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (m)	D, L (mm)	W (mm)	1.004		187.500	185.672	0.000	0	0																																																	
Outfall Pipe Number	Outfall Name	C. Level (m)	I. Level (m)	Min I. Level (m)	D, L (mm)	W (mm)																																																														
1.004		187.500	185.672	0.000	0	0																																																														
<u>Simulation Criteria for Storm</u> <table><tbody><tr><td>Volumetric Runoff Coeff</td><td>0.750</td><td>Additional Flow - % of Total Flow</td><td>0.000</td></tr><tr><td>Areal Reduction Factor</td><td>1.000</td><td>MADD Factor * 10m³/ha Storage</td><td>2.000</td></tr><tr><td>Hot Start (mins)</td><td>0</td><td>Inlet Coefficient</td><td>0.800</td></tr><tr><td>Hot Start Level (mm)</td><td>0</td><td>Flow per Person per Day (l/per/day)</td><td>0.000</td></tr><tr><td>Manhole Headloss Coeff (Global)</td><td>0.500</td><td>Run Time (mins)</td><td>60</td></tr><tr><td>Foul Sewage per hectare (l/s)</td><td>0.000</td><td>Output Interval (mins)</td><td>1</td></tr><tr><td>Number of Input Hydrographs</td><td>0</td><td>Number of Storage Structures</td><td>0</td></tr><tr><td>Number of Online Controls</td><td>1</td><td>Number of Time/Area Diagrams</td><td>0</td></tr><tr><td>Number of Offline Controls</td><td>0</td><td>Number of Real Time Controls</td><td>0</td></tr></tbody></table>						Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000	Areal Reduction Factor	1.000	MADD Factor * 10m³/ha Storage	2.000	Hot Start (mins)	0	Inlet Coefficient	0.800	Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000	Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60	Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1	Number of Input Hydrographs	0	Number of Storage Structures	0	Number of Online Controls	1	Number of Time/Area Diagrams	0	Number of Offline Controls	0	Number of Real Time Controls	0																											
Volumetric Runoff Coeff	0.750	Additional Flow - % of Total Flow	0.000																																																																	
Areal Reduction Factor	1.000	MADD Factor * 10m³/ha Storage	2.000																																																																	
Hot Start (mins)	0	Inlet Coefficient	0.800																																																																	
Hot Start Level (mm)	0	Flow per Person per Day (l/per/day)	0.000																																																																	
Manhole Headloss Coeff (Global)	0.500	Run Time (mins)	60																																																																	
Foul Sewage per hectare (l/s)	0.000	Output Interval (mins)	1																																																																	
Number of Input Hydrographs	0	Number of Storage Structures	0																																																																	
Number of Online Controls	1	Number of Time/Area Diagrams	0																																																																	
Number of Offline Controls	0	Number of Real Time Controls	0																																																																	
<u>Synthetic Rainfall Details</u> <table><tbody><tr><td>Rainfall Model</td><td>FSR</td><td>Profile Type</td><td>Summer</td></tr><tr><td>Return Period (years)</td><td>30</td><td>Cv (Summer)</td><td>0.750</td></tr><tr><td>Region</td><td>England and Wales</td><td>Cv (Winter)</td><td>0.840</td></tr><tr><td>M5-60 (mm)</td><td>19.000</td><td>Storm Duration (mins)</td><td>30</td></tr><tr><td>Ratio R</td><td>0.339</td><td></td><td></td></tr></tbody></table>						Rainfall Model	FSR	Profile Type	Summer	Return Period (years)	30	Cv (Summer)	0.750	Region	England and Wales	Cv (Winter)	0.840	M5-60 (mm)	19.000	Storm Duration (mins)	30	Ratio R	0.339																																													
Rainfall Model	FSR	Profile Type	Summer																																																																	
Return Period (years)	30	Cv (Summer)	0.750																																																																	
Region	England and Wales	Cv (Winter)	0.840																																																																	
M5-60 (mm)	19.000	Storm Duration (mins)	30																																																																	
Ratio R	0.339																																																																			
©1982-2017 XP Solutions																																																																				

3E Consulting Engineers Ltd		Page 3
4 Calder Close Wakefield WF4 3BA		
Date 12/06/2017 11:31 File Full SW Model.MDX	Designed by john.mitchell Checked by	
Micro Drainage Network 2017.1.1		
Online Controls for Storm Orifice Manhole: 5, DS/PN: 1.004, Volume (m³): 8.3 Diameter (m) 0.036 Discharge Coefficient 0.600 Invert Level (m) 185.760		
©1982-2017 XP Solutions		