



GENERAL SAFETY NOTES

- WHERE THE ROAD BASES HAVE BEEN USED AS A TEMPORARY RUNNING SURFACE DURING THE CONTRACT IT SHALL BE THOROUGHLY CLEANED AND POWER WASHED AS NECESSARY AFTER DRYING AND IMMEDIATELY BEFORE THE REINFORCEMENT AND A 100mm COAT OF BITUMEN MASTIC SHALL BE APPLIED TO THE ROAD SURFACE.
- ALL JOINTS AND JOINTS SHALL BE COVERED WITH A 100mm COAT OF BITUMEN MASTIC.
- ALL JOINTS AND JOINTS SHALL BE COVERED WITH A 100mm COAT OF BITUMEN MASTIC.

HEALTH & SAFETY

- CONTRACTOR SHOULD BE AWARE OF GENERAL CONSTRUCTION RISKS TO PREVENT SLIPS, TRIPS AND FALLS AND THE NECESSARY PRECAUTIONS TO PREVENT SUCH RISKS.
- CONTRACTOR SHOULD BE AWARE OF GENERAL CONSTRUCTION RISKS TO PREVENT SLIPS, TRIPS AND FALLS AND THE NECESSARY PRECAUTIONS TO PREVENT SUCH RISKS.

ROADS & LANEWAYS

- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.
- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.

CAUTION

- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.
- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.

ENVIRONMENTAL

- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.
- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.

DRAINAGE SPECIFICATIONS FOR YORKSHIRE WATER

- ALL ADAPTABLE SEWER WORKS AND MATERIALS TO BE IN ACCORDANCE WITH 'CODE FOR ADOPTION'.
- ALL ADAPTABLE SEWER WORKS AND MATERIALS TO BE IN ACCORDANCE WITH 'CODE FOR ADOPTION'.

OTHER DRAINAGE NOTES

- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.
- CONTRACTOR TO PROVIDE FENCING TO PROTECT THE WORK AREA AND ENSURE THAT ANY ROAD REMAINS SAFE DURING THE WORK.

DRAINAGE SUMMARY

SURFACE WATER

- EXISTING SURFACE WATER
- EXISTING SURFACE WATER

FOUL WATER

- EXISTING FOUL WATER
- EXISTING FOUL WATER

DESIGN NOTES

- ALL WORKS TO COMPLY WITH CURRENT VERSION OF THE FOLLOWING DOCUMENTS:
- ALL WORKS TO COMPLY WITH CURRENT VERSION OF THE FOLLOWING DOCUMENTS:

DRAINAGE NOTES

- ALL PRIVATE FOUL WATER PIPES NOT ANNOTATED TO BE A MINIMUM OF 1000mm INSTALLED AT 1:40.
- ALL PRIVATE FOUL WATER PIPES NOT ANNOTATED TO BE A MINIMUM OF 1000mm INSTALLED AT 1:40.

PIPE MATERIALS

- 150mm CLAY PIPES TO BE 800mm MARKED AND CERTIFIED TO BS 2684 & BS 2684.
- 150mm CLAY PIPES TO BE 800mm MARKED AND CERTIFIED TO BS 2684 & BS 2684.

KEY

FLOOD ROUTE DIRECTIONS BASED UPON ANY POTENTIAL BLOCKAGES WITHIN THE SURFACE WATER DRAINAGE SYSTEM AND/OR ANY FLOODING AS IDENTIFIED WITHIN THE DRAINAGE MODELLING AT 100YR/40% CC EVENT

SUBJECT TO APPROVAL BY THE LOCAL AUTHORITY

PRELIMINARY

CLIENT: HARWORTH GROUP

PROJECT: GATEWAY 36, BIRDWELL UNIT 4 (PLOT 8)

TITLE: DRAINAGE LAYOUT PLAN SHEET 2 OF 2

DATE: 16.11.2022

JOB NO: Y22039

DRAWN: D200

CHECKED: AMF

DATE: 16.11.2022

REV: 1