





SURFACE WATER NON MAN-ENTRY INSPECTION CHAMBER TYPE G
450mm Ø SHAFT FOR USE WITH 110mm, 160mm OR 150mm (VIA ADAPTOR) PIPES
MAX DEPTH FROM COVER LEVEL TO INVERT OF PIPE 3.0m
(NOT TO SCALE)



FOUL NON MAN-ENTRY INSPECTION CHAMBER TYPE J
460mm Ø SHAFT FOR USE WITH 110mm, 160mm OR 150mm PIPES
MAX DEPTH FROM COVER LEVEL TO INVERT OF PIPE 2.0m
(NOT TO SCALE)




DRAINS WITH CONCRETE PROTECTION



APPLICABLE UNDER ROADS / SERVICE YARDS AND WHERE DRAINS HAVE LESS THAN 1200mm COVER ALSO APPLICABLE UNDER LANDSCAPE AND PRIVATE DRIVE AREAS WHICH HAVE LESS THAN 600mm COVER.

DRAINS WITH FLEXIBLE (TYPE S) BED AND SURROUND



APPLICABLE UNDER ROADS / SERVICE YARDS AND WHERE DRAINS HAVE MORE THAN 1200mm COVER ALSO APPLICABLE UNDER LANDSCAPE AND PRIVATE DRIVE AREAS WHICH HAVE MORE THAN 600mm COVER.

TYPE S APPLICABLE UNDER FOOTPATHS VERGES AND OTHER NON TRAFFICKED AREAS WHERE DRAINS HAVE MORE THAN 600mm COVER.


KEY:

- HIGHWAY CONSTRUCTION
- SELECTED EXCAVATED MATERIAL SHALL BE PLACED IN NO GREATER THAN 225mm LAYERS COMPLYING WITH THE CIVIL ENGINEERING SPECIFICATION WITHIN SEWERS OF ADOPTION 6TH EDITION REF 5.3.4
- GRANULAR BEDDING AND SURROUND MATERIAL 20mm NOMINAL SINGLE SIZE
- LANDSCAPE AREA
- CONCRETE SURROUND TO BE GEN3 C20
- GRANULAR SUB-BASE MATERIAL (TYPE 1) DEPOSITED IN LAYERS NOT EXCEEDING 225mm IN UNCONSOLIDATED LAYERS AND THEN FULLY COMPACTED UNLESS STATED.


MINIMUM TRENCH WIDTHS (EN 1610)		
PIPE DIAMETER	AGGREGATE	
	NOMINAL SINGLE SIZE	GRADED
UP TO 100mm	10mm	
100mm TO 150mm	10mm 14mm	14mm TO 15mm
150mm TO 300mm	10mm 14mm 20mm	14mm TO 5mm 20mm TO 5mm
300mm TO 550mm	14mm 20mm	14mm TO 5mm 20mm TO 5 mm
OVER 550mm	20mm 40mm	14mm TO 5mm 20mm TO 5mm 40mm TO 5mm

MINIMUM TRENCH WIDTHS (EN 1610)	
PIPE DIAMETER	SUPPORTED TRENCH
UP TO 255mm	OUTSIDE PIPE DIAMETER + 400mm
225mm TO 350mm	OUTSIDE PIPE DIAMETER = 500mm
350mm TO 700mm	OUTSIDE PIPE DIAMETER + 700mm
700mm TO 1200mm	OUTSIDE PIPE DIAMETER + 850mm
OVER 1200mm	OUTSIDE PIPE DIAMETER + 1000mm

POLYSTORM ATTENUATION CRATES DETAIL
SCALE 1:10



POLYSTORM ATTENUATION CRATES PLAN VIEW
SCALE 1:50



THIS DOCUMENT HAS BEEN PREPARED IN ACCORDANCE WITH THE SCOPE OF INSPIRE DESIGN & DEVELOPMENT LTD'S APPOINTMENT WITH ITS CLIENT AND IS SUBJECT TO THE TERMS OF THAT APPOINTMENT. INSPIRE DESIGN & DEVELOPMENT LTD ACCEPTS NO LIABILITY FOR ANY USE OF THIS DOCUMENT OTHER THAN BY ITS CLIENT AND ONLY FOR THE PURPOSES FOR WHICH IT WAS PREPARED AND PROVIDED. © INSPIRE DESIGN & DEVELOPMENT LTD 2025



CLIENT:
OAK AND PROSPER
CONSTRUCTION LTD

PROJECT:
PARK ROAD, WORSBROUGH

DRAWING TITLE:
INSPECTION CHAMBER &
ATTENUATION
CONSTRUCTION DETAILS

DRAWING STATUS:
FOR APPROVAL

DRAWN:
NGP

CHECKED:
CR

APPROVED:
CR

DATE:
07/03/2025

DRAWING No.:

OP-1803-01-DR-004

SCALE @ A1:

N.T.S

REVISION No.:

REV DATE NAME CHECK NOTE