Report No: C398 Rev A Date: September 2022

LAND OFF PADDOCK ROAD, STAINCROSS, BARNSLEY, SOUTH YORKSHIRE MINING INVESTIGATION REPORT



Prepared for Andrew Bailey Architects

Prepared by G&M Consulting Ltd, The Chestnuts, Brackenhill Road, Haxey, Doncaster DN9 2LR





REPORT NUMBER:	C398	REPORT STATUS:	Final – Rev A
REPORT TYPE:	Mining investigation Report		
REPORT DATE:	September 2022		
SITE:	Land off Paddock Road, Staincross Barnsley, South Yorkshire		
PREPARED FOR:	Andrew Bailey Architects		
PREPARED BY:	A Swinbourne BSc. (Hons), MIEnvSc, FGS, ACIEH.		
REVIEWED BY:	G Swinbourne BSc. (Hons), MSc., DIC, FGS		

This report is written for the sole use of Andrew Bailey Architects or their client. No other third party may rely on or reproduce the contents of this report without the written approval of G&M. If any unauthorised third party comes into possession of this report, they rely upon it entirely at their own risk and the authors do not owe them any of Duty of Care or Skill.

TABLE OF CONTENTS

TABLE OF CONTENTS	1
1.0 INTRODUCTION.	2
2.0 BACKGROUND INFORMATION.	
2.1 Site Description	
2.2 Geology	
2.3 Coal Mining Risk Assessment	
3.0 FIELDWORK	
3.1 Scope of Works	5
3.2 Trial Pits	
4.0 GROUND CONDITIONS	6
5.0 DISCUSSIONS AND CONCLUSIONS	

APPENDICES

APPENDIX A – DRAWINGS

APPENDIX B – EXPLORATORY HOLE RECORDS

APPENDIX C – COAL AUTHORITY PERMIT


APPENDIX D - PHOTOGRAPHIC RECORD

LAND OFF PADDOCK ROAD, STAINCROSS, BARNSLEY, SOUTH YORKSHIRE MINING INVESTIGATION REPORT

1.0 INTRODUCTION.

G&M Consulting Ltd (G&M) was commissioned by Andrew Bailey Architects to carry out a ground investigation and geotechnical appraisal of a site off Paddock Road, Staincross, Barnsley, South Yorkshire. Part of the work is an investigation into the effects of historical mining on the site. This report deals with the historical mining element.

It is understood that outline planning approval (2017/1387) has been granted by Barnsley Metropolitan Borough Council for the demolition of existing dwelling and outbuildings and erection of up to 6 dwellings. The proposed development layout is shown on Drawing No RB2/2020- PA 02D, prepared by Andrew Bailey Architects; a copy of this drawing is shown below.



This investigation also covers the area of proposed development to the south of the above permission, as shown on the red line boundary above. The proposed development layout of this area is shown on Drawing No RMH-P02Rev J dated June 2022, prepared by Andrew Bailey Architects, a copy of which is presented in Appendix A of this report.

The objective of this work was to establish the ground profile by means of an intrusive ground investigation in across the site and to determine the possible risk from shallow mine workings. The work comprised the excavation of trial pits and trial site scrape and the drilling of rotary boreholes. and the preparation of this report, which contains a description of the site and the works carried out, and the exploratory hole logs.

The scope of the ground investigation was based on a Coal Mining Risk Assessment (CMRA) prepared by G&M Ref C398 dated October 2020. This report should be read in conjunction with the CMRA, however, salient points from the CMRA are presented in Section 2.3 of this report.

The ground investigation has been carried out using intrusive ground investigation techniques in general accordance with the recommendations of BS5930: 2015 + A1: 2020 *Code of practice for ground investigations*, which maintains compliance with BS EN 1997-1 and 1997-2 and their related standards. Whilst every attempt is made to record full details of the strata encountered in the exploratory holes, techniques of hole formation and sampling will inevitably lead to disturbance, mixing or loss of material in some soils and rocks.

All information, comments and opinions given in this report are based on the ground conditions encountered during the site work, and on the results of laboratory and field tests performed during the investigation.

However, there may be conditions at the site that have not been taken into account, such as unpredictable soil strata and water conditions between or below exploratory holes. It should be noted that groundwater levels usually vary due to seasonal, atmospheric and/or other effects and may at times differ to those measured during the investigation.

This report is intended for the sole use of Andrew Bailey Architects or their client. No other third party may rely upon or reproduce the content of this report without written authorisation of the report author. If any unauthorised third party comes into possession of this report they rely on it at their own risk and the author does not owe them any Duty of Care or Skill

2.0 BACKGROUND INFORMATION.

2.1 Site Description

The site is located approximately 4 km North of Barnsley Town centre. It is within the village of Staincross on the northern side of the valley of the River Dearne. The National Grid Reference for the approximate centre of the site is SE 334102.

The site is an irregular plot of land covering an area of approximately 2.3 hectares. It fronts to the north on to Paddock Lane where it is only a narrow plot of land approximately 20 m wide and running south for approximately 90m before widening out into a larger L shape plot of land. One limb of the L is approximately 190 m by 70 m with the long axis aligned east west. The second limb is at the eastern end of the first and extends to the south, it is approximately 175 m by 55 m with the long axis aligned north south. The narrow stripe off Paddock Lane is occupied by a number of buildings associated with Woodview Farm. The remaining area of the site is open fields / scrub land.

The overall fall in ground level across the site from Paddock Lane to the most southerly point is approximately 20 m and that from Paddock Lane to the southern edge of the east west trending section of the site 12 m.

The site is bordered to the north by the gardens of residential properties that front on to Paddock Lane or associated side roads, to the west and south by a mixture of open spaces and residential properties and to the east by fields and allotments.

2.2 Geology

Information on the geology of the site was obtained from the following sources published by the British Geological Survey (BGS):

- BGS map (England & Wales 1:50,000 Scale, Sheet 87 Barnsley, Bedrock & Superficial Edition, 2008).
- BGS online Geoindex http://mapapps2.bgs.ac.uk/geoindex/home.html
- The BGS Lexicon of Named Rock Units, which provides typical descriptions for most geological units (www.bgs.ac.uk/lexicon).

The above geological records for the area, show the site to be underlain by strata of the Pennine Middle Coal Measures Formation (PMCM) which comprises interbedded mudstone, siltstone and sandstone with coal seams.

The northern edge of the site is shown underlain by the Wooley Edge Rock a named sandstone within the PMCM. To the south two coal seams are shown to outcrop within the site. The outcrops are aligned generally east west with a dip to the north east. The most northerly of the two seams is the Meltonwood Coal. The second seam which outcrops further south is the Two Foot Coal.

The stratigraphic column from the 1:50,000 geology map shows the following descending sequence of coal seams likely to affect the site:

Coal Seam	Seam Thickness (m)	Estimated Thickness between seams (m)	Comments
Meltonwood Coal	0 - 2.3		Discontinuous
		5	
Meltonfield Coal	0 - 1.4		Discontinuous
		10	
Two Foot Coal	0.1 - 2.1		
		30	Discontinuous
Abdy (Winter) Coal	0 - 1.9		

Three of the seams are shown discontinuous across the area of the map. The estimated thickness of strata between the seams is based on the stratigraphic column.

The Abdy Coal is shown to outcrop in the valley side to the south of the site.

Areas of infilled ground are shown associated with the outcrops of the Two Foot Coal and the Abdy Coal to the east and south east of the site.

A fault is shown north of the site within the Wooley Edge Rock. It is aligned north-west south-east with a down throw to the north-east.

No superficial deposits are shown to be present on site.

2.3 Coal Mining Risk Assessment

As part of the CMRA a Consultants Coal Mining Report (CCMR) was obtained from the Coal Authority (CA). The following sections from the CMRA are considered salient points in scoping the ground investigation.

- The geological maps show two seams outcropping within the site the Meltonwood Coal and the Two-Foot Coal. The CCMR also shows the two seams outcropping as the Meltonfield Coal and the Two Foot Coal.
- The dips of the coal seams recorded as worked beneath the site in CCMR are approximately 5° to the north east.
- Given what is considered a high risk of shallow mine workings being present beneath the northern part of the site it is recommended that an intrusive ground investigation be carried out using rotary drilling techniques to confirm the depth to the various coal seams. A minimum of seven boreholes is suggested for an initial investigation..
- If as suggested bell pits or opencast workings are present close to the outcrops then rotary drilling may not encounter voids, only loose ground and the absence of coal. To this end additional

boreholes may be needed to confirm the depth of intact coal i.e. to identify the level of the seam or alternatively trial trenches are carried out to locate the out crops and investigate any crop workings.

3.0 FIELDWORK.

3.1 Scope of Works

The field work was carried out in phases between 4th November 2020 and 15th February 2021 and comprised trial pits, trial site scrapes and rotary boreholes shown on the Trial Pit and Site Strip Location Plan (drawing number C398/CM/01) and Borehole Location Plan (drawing number C398/CM/02) presented in Appendix A of this report:

SCOPE OF INTRUSIVE WORKS AND IN-SITU TESTING										
Number	Exploratory Hole	Hole / Test Numbers	Notes							
18	Trial pits	TP1 to TP18	Phase 1 04/11/2020 to 05/11/2020							
			Phase 2 15/02/2021							
2	Trial site scrape	TT1 and TT2	Carried out 15/02/2021							
8	Rotary drilled open holes	BH1 to BH8	05/01/2021 to 07/01/21							

The scope of the works and the exploratory positions were selected by G&M and adjusted where necessary to take account of buried or overhead services, or other restrictions.

Prior to the commencement of any exploratory hole a scan was carried out for buried services using a combination of cable avoidance tool (CAT) and signal generator ('Genny').

All of the locations were accurately surveyed using a Leica GPS system.

The trial pits and site scrapes were logged by an engineer in accordance with the recommendations of BS5930:2015+ A1: 2020. Detailed descriptions, together with relevant comments are given on the respective logs, presented in Appendix B of this report. The rotary open holes were logged by the driller, copies of the drillers logs are presented in Appendix B.

3.2 Trial Pits

The trial pits were excavated using a 6-tonne tracked excavator equipped with 0.5 m wide bucket. The primary aim was for geotechnical /geoenvironmental purposes but also to determine the depth to rock head and expose any coal outcrops.

3.3 Trial Site Scrape

A localised site scrape was undertaken using a 6-tonne tracked excavator to a maximum depth of 0.15 m using a ditching bucket to scrap away the topsoil and subsoil to expose the upper surface of the weathered rock (weathered mantle material) to determine if there was any discolouration which could be indicative of shallow mine workings such as bell pits or open cast / crop workings. The extent of this scrape is shown on the Trial Pit and Site Strip Location Plan (drawing number C398/CM/01) presented in Appendix A of this report:

A photographic record of the site scrape is presented in Appendix D of this report.

3.4 Rotary Boreholes

The drilling work was undertaken by Cape Site Services using a Beretta T25 tracked rotary drilling rig and carried out under the Terms and Conditions of the CA Permission No 20241, a copy of which is presented in Appendix C of this report.

Drilling was initially progressed using 150mm diameter augers through the superficial soils, and cased into the underlying bedrock, to aid flush returns.

Drilling was undertaken using water flush or air/mist. In accordance with the CA permission, the boreholes were monitored at surface for gases, during their advancement. The boreholes were backfilled on completion.

4.0 GROUND CONDITIONS.

The sequence of strata encountered during this investigation generally confirms published geological information for the area of strata of the Pennine Middle Coal Measures overlain locally by made ground.

Made Ground

Topsoil is present across much of the site. Made ground was only encountered in four trial pits TP1, TP2, TP13 and TP18 to depths of between 0.20 m and 1.20 m. In general, it comprises either a gravelly clay or clayey gravelly sand. The gravel content generally comprises a mixture of fragments of brick, mudstone, sandstone and concrete with fragments of coal noted in TP1 and TP13.

Weathered Coal Measures Deposits

The topsoil and made ground (where present) is underlain by firm to stiff gravelly clay, which contains with depth lithorelics of the underlying rock. This material is typical of the weathering in situ of the underlying bedrock.

Pennine Middle Coal Measures Deposits

Bedrock comprises an interbedded sequence of mudstone and sandstone with four coal seams encountered across the site. The boreholes in which the coals were encountered together with depths and thicknesses are summarised in the following table and on the geological cross section presented in Appendix A of this report.

Coal	Number of holes	<u>Thicl</u>	<u>kness</u>	<u>Comment</u>
		<u>Seam</u>	Intervening Strata	
Melton Field	BH8	0.5		
	TP1	0.7		
			10.2	
Two Foot	BH1-BH5 & BH6-BH8	0.4-0.5 (1.0)		1.0 m thickness proved in BH8
	TP7, TP16 & TP7	0.3-0.65		
			10.1-11.4	
Abdy Coal	BH1-BH8	0.8-0.9 (0.1)		0.1 m thickness assumed in BH4, black mudstone
			9.4	
Beamish	BH4	1.0		

Prepared for: Andrew Bailey Architects

The most northerly seam is assumed to be the Meltonfield, as shown in Coal Authority records in the CMRA, although the geological map shows it as the Meltonwood coal. It outcrops close to the northern edge of the site and the two foot outcrops through the central area of the site as anticipated from the records presented in the CMRA. Both these outcrops were proven in one or more of the trial pits.

The seam assumed to be the Abdy coal is likely to outcrop close to the southern border of the site. This seam was not clearly identified in BH4. All the other boreholes proved between 0.8 m and 0.9 m of coal where in BH4 only 0.1 m of black mudstone was recorded at the anticipated level. The absence of the coal could be due to being close to the outcrop, or the presence of a washout within the geology. No loss of flush or broken / soft ground was recorded in the vicinity of the mudstone in BH4 to indicate working of the coal although ground water was encountered at a depth of 6m.

Mining

No evidence of historical mining was encountered during the investigation. Where coal was encountered in the boreholes and trial pits it was intact. No loss of flush, broken ground or voids were recorded in the boreholes. The trial site scrape did not encounter any evidence of surface workings, either bell pits or backfilled open cast.

The site slopes to the south and the coal seams dip to the north east, therefore the coal seams become deeper relatively quickly to the north or north east away from the outcrop of the seam. There will be a zone approaching the out crop where the coal seam would be in influencing distance of the surface. The general rule of thumb for assessing the depth of influence, from pillar and stall coal mining, is the 10 x the worked seam thickness rule. For a site not to be affected by mining the seam needs to be overlain by a thickness of competent bedrock equal to or greater than 10 x the seam thickness. For the Two Foot coal and the Abdy coal the horizontal distance back from the outcrop that a zone of influence may extend is estimated to be about 70 m. The Meltonfield is likely to be in influencing depth where it is present beneath the northern area of the site. This rule is a guide only and does not take in to account the effect of multiple seams having been worked beneath a site.

5.0 DISCUSSIONS AND CONCLUSIONS

In accordance with the instruction issued by Andrew Bailey Architects, an intrusive investigation has been carried out to investigate the possible mining legacy at the site off Paddock Road, Staincross Barnsley.


The results from this investigation suggests that shallow mining has not taken place beneath the site. No evidence of mining was encountered in any of the exploratory holes. Given the size of the site and the number of exploratory holes it is feasible that localised mining has taken place in areas not investigated and as such a watching brief should be maintained whilst foundations are excavated, particularly in the areas close to the outcrops and the area of potential zone of influence discussed above. If any discolouration or deep made ground is encountered then a suitably experienced and qualified consultant should be notified and the area inspected prior to continuing.


This report should be submitted to the local authority for their comment/approval, prior to undertaking any development work.





APPENDIX A

DRAWINGS











		Scale NTS					
Contract	C398 – Paddock Road, Staincross	Drawn AS	Approved GS				
	Stailleiuss	Drawing Name – Coal Cross Section					
Client – Andrew Bailey Architects							



APPENDIX BEXPLORATORY HOLE RECORDS

Trial Pit Record					No ract No	1 C398		
Method:	Machine exca	achine excavated trial pit Site				ate	04/11/20	
	using a 3 tonne rated tracked excavator		using a 3 tonne rated 28 Paddock Road, Staincross		Scale		1:25	
			Client	Andrew	Bailey Architects	Logged By		ATS
Туре	Sample Deta Depth	ils Vane	1		-	-	Level	
1,750	To-from (m)	kN/m²		Desc	cription	Depth (m)	(mAOD)	Legend
				s subangular fine	ork grey very gravelly CLAY. to coarse of brick, concrete	0.20		
			gravelly		w mottled light grey silty subangular fine to coarse of	0.80		
			fracture noted al slightly	d COAL. Occasion long fracture surfa	vitreous extremely closely nal brown iron staining ices Recovered as: Black angular fine to coarse gravel			
			Firm ligi	nt grey very grave	lly CLAY. Gravel is	1.50		
				ular fine to coarse	of mudstone lithorelicts. /			
No ground Pit dimens Trial Pit us	ble during exca dwater encount sions 0.50x1.30 sed for soakaw ackfilled upon o	ered)m ay testing		Sample Types D - Disturbed B - Bulk	W - Water ES - Environmental		GG	M

			No No	2 C398			
Made	Maakins	Nato d 4=1 - 1 : 1	lo:			Contract No Date	
Method:		nchine excavated trial pit Site ng a 3 tonne rated 28 Paddock Road, Staincross					04/11/20
	tracked exca				S	cale	1:25
			Client	Andrew Bailey Architects	Logg	ged By	ATS
T	Sample Deta			, and on Balley , a difficulties		Laural	
Type	Depth To-from (m)	Vane kN/m²		Description	Depth (m)	Level (mAOD)	Legend
Hv	0.70	72,74,68	fine to c Gravel s of brick concrete	GROUND: Dark brown very clayey gravelly coarse SAND with a low cobble content. sized fragments are subangular fine to coarse and mudstone. Cobbles are subangular of e and sandstone.	0.65		
			gravelly mudstor	ally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular fine to coarse of ne lithorelicts. tely strong thinly laminated to very thinly	1.45		
Remarks			bedded	SÁNDSTONE. Recovered as slightly gravelly plan cobbles. Trial pit complete at 1.50m Sample Types			
Faces sta No ground Pit dimens	ble during exc dwater encoun sions 0.50x1.4 ackfilled upon I Vane	tered 0m		D - Disturbed W - Water B - Bulk ES - Environmental		GAL	M

Trial Pit Record					No	3	
lethod: Machine excavated trial pit						ract No	C398
flethod:	using a 3 tonr	ne rated	Site	28 Paddock Road, Staincross	Date Scale		04/11/20 1:25
	tracked exca	/ator	Client	Andrew Bailey Architects		ged By	ATS
Type	Sample Deta Depth	ils Vane				Level	
1,700	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legeno
			Dark br (TOPS	own very sandy CLAY. Sand is fine to coarse. OIL)	0.35		
Hv D	0.70 0.80	92,94,98	gravelly	cally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular fine to coarse of ct mudstone.			
Hv	1.00	88,92,90	iid ioi oik	or mudotono.	1.05		
D	1.20			cally stiff dark grey locally light grey very			
Hv	1.50	82,92,96		CLAY. Gravel is subangular fine to coarse of ne lithorelicts	1.70		
			MUDS1 subang	lark grey thinly to thickly laminated FONE: Recovered as yellowish brown ular fine to coarse gravel with a low cobble . Cobbles are subangular. Trial Pit Complete at 1.80m			
lo ground it used fo	ble during exca dwater encount or soakaway te ackfilled upon o	tered esting	soakawa	Sample Types D - Disturbed W - Water B - Bulk ES - Environmental ay Hv - Hand vane		GA	M

	Trial Pit Record						4
Mothod	Machine eve	avated trial pit	Qi+^		Contract No Date		C398 04/11/20
wietnou.	using a 3 ton tracked exca	ne rated	Site	28 Paddock Road, Staincross		Scale	
	Sample Deta		Client	Andrew Bailey Architects	Logo	jed By	ATS
Type	Depth	Vane kN/m²		Description	Danth (m)	Level	
	To-from (m)	KN/M			Depth (m)	(mAOD)	Legend
			(TOPS	own very sandy CLAY. Sand is fine to coarse. OIL)	0.30		
Hv	0.65	110,98,102	gravelly	cally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular fine to coarse of ne lithorelicts.			
	t				1.05		
	-			tely weak brownish orange thinly laminated to	1		
	1			nly bedded SANDSTONE: Recovered as clayey very sandy subangular fine to coarse			
	Ì			with a low cobble and boulder content.			
D	1.60		Cobble	s and boulders are subangular. Trial pit complete at 1.60m			
Sow ingre Pit dimens	sions 0.50x1.4 ackfilled upon	o put at 1.35m 0m	n-No rise	Sample Types D - Disturbed W - Water B - Bulk ES - Environmental		GS	M

			^o No	5			
						ract No	C398
Method:		avated trial pit	Site	00 P. H. J. P. J. O. J.	D	ate	04/11/20
	using a 3 ton tracked exca			28 Paddock Road, Staincross	S	cale	1:25
	iraonoa oxoa	vator	Client		Logo	Logged By	
	Sample Deta	ails		Andrew Bailey Architects		Logged By	
Type	Depth	Vane		Description		Level	
	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legend
Hv	0.60	130,126,120	gravelly	cally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular fine to coarse of ct mudstone.	0.60		
			laminate subang	ely weak yellowish brown thinly to thickly ed MUDSTONE: Recovered as slightly clayey ular fine to coarse gravel with a low cobble . Cobbles are subangular.			
	•				1.50		
	•		Extreme	ely weak dark grey thinly to thickly laminated			
				ONE: Recovered as subangular fine to			
	•		coarse	gravel with a low cobble and boulder content.			
			Cobbles	s and boulders are subangular.			
	= •			Trial pit complete at 1.80m			
No ground Pit dimens	le during excu water encoun ions 0.50x1.4 ckfilled upon	itered 0m		Sample Types D - Disturbed W - Water B - Bulk ES - Environmental		GAL	M

		TF	TP No					
				Record		Contract No		
Method:		avated trial pit	Site	00 Daddada Daad Otsinaasa		Date		
	using a 3 ton tracked exca		28 Paddock Road, Staincross Sc		Scale			
	tracked exca	vator	Client		Log	ged By	ATS	
	Sample Deta	ails		Andrew Bailey Architects		, ,		
Type	Depth	Vane	Description			Level		
	To-from (m)	kN/m ²		Description	Depth (m)	(mAOD)	Legend	
			yellow s	ff indistinctly fissured light grey mottled pale slightly gravelly silty CLAY. Gravel is ular fine to coarse of lithorelict mudstone.	0.45			
							XX	
				L. L. L. L. LANDROTONE W				
				ely weak interbedded MUDSTONE with e: Recovered as locally slightly clayey sand	v			
				ular fine to coarse gravel with a low cobble				
			content	. Cobbles are subangular to subrounded.			XX	
	}							
				Trial pit complete at 1.50m				
No ground Pit used fo	l ble during exco dwater encoun or soakaway te sions 0.50x1.5	itered esting		Sample Types D - Disturbed W - Water B - Bulk ES - Environmental	l	GS	M FING	

		Tria	al Pit	Record		No No	7
						ract No	C398
Method:	Machine excausing a 3 tonr	ne rated	Site	28 Paddock Road, Staincross		ate cale	05/11/20 1:25
	tracked exca		Client	Andrew Bailey Architects		ged By	ATS
Туре	Sample Deta Depth	ils Vane				Level	
.,,,,,	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legend
HV	0.40	58,52,50	CLAY.	le yellow mottled light grey silty gravelly Gravel is subangular fine to coarse of ct mudstone.			
D HV	0.60 0.70	74,70,78			0.70		
D	1.10			cally stiff, dark grey gravelly CLAY. Gravel is ular fine to coarse of lithoretict mudstone.			
					1.35		
			fracture noted a slightly	eak to weak black vitreous extremely closely and COAL. Occasional brown iron staining long fracture surfaces Recovered as: Black clayey sandy subangular fine to coarse gravel agments.			
	-			ght grey very gravelly CLAY. Gravel is	2.00		
				Trial pit complete at 2.10m			
Remarks Sides stat	ole during exca	vation		Sample Types D - Disturbed W - Water			
No ground Pit dimens	dwater encount sions 0.50x1.40 ackfilled upon o	tered Om		B - Bulk ES - Environmental		CONSULT	FING

		Tri	al Pit	Record			No	8
Matter !	Machina	wata d 4! - 1	i+10:-				ract No	C398
Method:	Machine exca using a 3 tonr		Site	28 Paddock F	Road, Staincross		ate	05/11/20
	tracked excav			20 : addock i	iouu, oiumoioss	S	cale	1:25
			Client	∆ndrew Ra	iley Architects	Logg	ged By	ATS
	Sample Deta			Andrew Bu	moy Aromitooto			
Type	Depth To-from (m)	Vane kN/m²		Descrip	otion	Depth (m)	Level (mAOD)	Legend
	10-110111 (111)	Kitiiii				Deptii (iii)	(IIIAOD)	— —
	į –							
					nottled light grey silty			
				CLAY. Gravel is sub- t mudstone.	angular fine to coarse of			
	<u> </u>		illi loi ello	t muustone.				
						0.70		
	-			e grey very gravelly C				
D	1.20		subangu	ılar fine to coarse of ı	mudstone lithorelicts.			
	ļ.		Fortune			1.40		
				ely weak, orangish br hinly bedded SANDS	rown thickly laminated to STONE: Recovered as			
	•				bangular fine to coarse			
				grave				
				Trial pit comple	te at 1.50m			
	-							
	•							
	1							
	•							
	-							
1	† l							
1	į l							
1	ļ l							
1								
1	ł l							
1								
	į l							
	ļ							
	-							
	†							
	† l							
D				0				
Remarks	ole during excu	vation		Sample Types D - Disturbed	W - Water		NEW T	
	dwater encount			D - Disturbed B - Bulk	ES - Environmental		G	M
Pit used for	or soakaway						CONSULT	ING
	sions 0.50x1.70)m					CONSUL	ING
							-	

		Tri	al Pit	Record			No	9
							ract No	C398
Method:	Machine excarusing a 3 tonn		it Site	28 Paddock P	oad, Staincross		ate	05/11/20
	tracked excav			20 T dudock N	oud, otaliici 033		cale	1:25
	Sample Detai	ilo	Client	Andrew Ba	iley Architects	Logo	ged By	ATS
Туре	Sample Detai Depth	Vane		Dagarin	4!		Level	
	To-from (m)	kN/m²	0.166.6	Descrip		Depth (m)	(mAOD)	Legend
			Stiff friable yellow mottled orangish yellow gravelly very sandy CLAY. Sand is fine to coarse. Gravel is					
				ular fine to coarse of r		0.30		
_								
D	0.50							
				cally stiff pale yellow m	nottled light grey silty angular fine to coarse of			
				ne lithorelicts.	angular line to coarse or			_
	+							
	<u> </u>					1.10		
	1				own thinly laminated to			
	+			nly bedded SANDSTC				
	<u> </u>			subangular fine to coar content. Cobbles are s				
			- Sobbie (
				Trial pit comple	te at 1.20m			
	-							
	-							
	1							
	†							
	-							
	-							
	-							
	+							
	-							
	+							
	-							
	_							
	-							
	-							
	+							
Remarks		ti		Sample Types	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			
	ole during excur dwater encount				W - Water ES - Environmental		G	M
Trial pit us	sed for soakawa	ay		_ Bain			CONSULT	ING
Pit dimens	sions 0.50x1.60)					CONSOL	
1								

		Tria	ıl Pit	Record		No No	10
NA - 41 - 1	IN 4 In its		lo.			ract No	C398
Method:	Machine excusing a 3 ton tracked exca		Site	28 Paddock Road, Staincross		cale	05/11/20 1:25
	irackeu exca	valui	Client		Logo	ged By	ATS
	Sample Deta	ails		Andrew Bailey Architects	9,	, <u>,</u>	
Type	Depth	Vane		Description		Level	
	To-from (m)	kN/m ²		- Besonption	Depth (m)	(mAOD)	Legend
HV D HV	0.40 0.50 0.60	58,52,62 108,110,110	gravelly	cally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular fine to coarse of ct mudstone.	0.80		
D	1.20		CLAY v subang	rk brown mottled bluish grey silty very gravelly with a low cobble content. Gravel is ular fine to coarse of lithrelict mudstone. s are subrounded of ironstone.			
Ì					1.60		
			Extreme	ely weak, light grey thinly to thickly laminated			
			MUDST	TONE: Recovered as sandy subangular fine to	 		
			coarse	gravel. Sand is fine to coarse.			
				Trial pit complete at 1.80m			
				mai pit complete at mooni			
Remarks				Sample Types			
No ground Pit dimens	ble during exc dwater encour sions 0.50x1.7 led upon comp	itered '0m		D - Disturbed W - Water B - Bulk ES - Environmental		Ge	TING

		Tri	al Pit	Record		P No	11
						ract No	C398
Method:	Machine exc using a 3 tor	avated trial p	It Site	28 Paddock Road, Staincross		ate	05/11/20
	tracked exca			20 Faudock Road, Stallicross	S	cale	1:25
			Client	A . I B. W A . I W A	Log	ged By	ATS
	Sample Det			Andrew Bailey Architects			
Type	Depth	Vane		Description		Level	
	To-from (m)	kN/m ²		2 00011,611	Depth (m)	(mAOD)	Legend
HV	0.60	82,78,70	gravelly	cally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular fine to coarse of ct mudstone.	0.70		
			CLAY w	k brown mottled bluish grey silty very gravelly with a low cobble content. Gravel is ular fine to coarse of lithrelict mudstone. s are subrounded.	1.40		
			Extreme	ely weak light grey thinly to thickly laminated			
				ONE: Recovered as sandy subangular fine to gravel. Sand is fine to coarse. Trial pit complete at 1.50m			
No ground Pit used fo	ole during exc dwater encour or soakaway t sions 0.50x1.1	ntered ests		Sample Types D - Disturbed W - Water B - Bulk ES - Environmental		GS	M

		Tria	al Pit	Record			No	12
Mothodi	Machina ayaa	voted trial =:	+ lo:4 -		\longrightarrow		ract No	C398 05/11/20
Method:	Machine excarusing a 3 tonn	e rated	Site	28 Paddock Road, Staincross	H		cale	1:25
	tracked excav	at∪i	Client		-+	Logo	ged By	ATS
	Sample Detai	ils	Silent	Andrew Bailey Architects	F	Logi	jou by	710
Type	Depth	Vane		December 11 and			Level	
	To-from (m)	kN/m²		Description		Depth (m)	(mAOD)	Legend
D	0.80		gravelly	cally stiff pale yellow mottled light grey si CLAY. Gravel is subangular to rounded se of lithorelict mudstone and ironstone.	d fine).70		
			CLAY w	k brown mottled bluish grey silty very gr vith a low cobble content. Gravel is ular fine to coarse of lithrelict mudstone. s are subrounded.	-	.40		
			Extreme	ely weak light grey thinly to thickly lamina	ated .			
				ONE: Recovered as sandy subangular gravel. Sand is fine to coarse. Trial pit complete at 1.50m	fine to			
Domosii:				Comple Types				
Remarks		vation		Sample Types D - Disturbed W - Water				
No ground Pit dimens	Remarks Sides stable during excuvation No groundwater encountered Pit dimensions 0.50x1.30m Pit backfilled upon completion			D - Disturbed W - Water B - Bulk ES - Environment	tal		GS	TING

		Tria	l Pit	Record			No	13
	INA - de in		la.				ract No	C398
Method:	using a 3 tor tracked exca	cavated trial pit nne rated	Site	28 Paddoo	ck Road, Staincross		ate cale	15.02.21 1:25
	Hacked Exca	avatoi	Client			Logo	ged By	ATS
	Sample Det	ails		Andrew	Bailey Architects		, ,	71.0
Type	Depth	Vane		Dage	vintion		Level	
	To-from (m)	kN/m²			ription	Depth (m)	(mAOD)	Legend
ES	0.10				ght brown slightly gravelly lar fine to coarse of	0.10		
HV	0.50	62,64,58	fine to d Gravel : of brick	coarse SAND with sized fragments ar and mudstone. Co	rown very clayey gravelly a low cobble content. re subangular fine to coarse obbles are subangular of With a low cobble content.			
D HV	1.00 1.10	112,110,106		s are subrounded	of limestone.	1.20		
			Stiff da	rk brown mottled I	ight grey silty very gravelly	1		
	1				subangular fine to coarse	4.50		
					h a low cobble content.	1.50		
	t		Cobbles	s are subangular o	of lithorelict mudstone.			
			MUDST	ONE: Recovered gravel. Sand is fine	thinly to thickly laminated as sandy subangular fine to e to coarse.			
Remarks	I			Sample Types		[
	ole during exc	uvation		D - Disturbed	W - Water			200
No ground Pit dimens	dwater encour sions 1.90mx0 led upon com	ntered 0.40m		B - Bulk	ES - Environmental		GONSULT	TING

		Tria	al Pit	Record		No No	14
						ract No	C398
Method:	Machine exca		Site		D	ate	15.02.21
	using a 3 toni tracked exca			28 Paddock Road, Staincross	S	cale	1:25
			Client	Andrew Bailey Architects	Log	ged By	ATS
Туре	Sample Deta Depth	ails Vane			-	Level	
Type	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legend
	•						
ES	0.30						
HV	0.40	60,61,34	Firm loca	ally stiff pale yellow mottled light grey silty			— —
D	0.50		gravelly	CLAY. Gravel is subangular to rounded fine			
			to coars	e of lithorelict mudstone and ironstone.			
HV	0.80	82,84,80					
110	0.00	02,04,00			0.90		
D	1.00		Stiff, dar	k brown mottled light grey silty very gravelly			— —
				ocally very clayey subangular fine to coarse			
	1			L of mudstone with a low cobble content. are subangular of lithorelict mudstone.	1.30		
			Copples	Trial Pit complete at 1.30m	1.30		
	- -						
	-						
	-						
Remarks			<u> </u>	Sample Types			
Sides stat No ground Pit dimens	ole during excu Iwater encoun sions 1.70mX0 ed upon comp	tered .40m	I	Sample Types D - Disturbed W - Water B - Bulk ES - Environmental		GEL	ING

		Tria	l Pit	Record		No	15
						ract No	C398
Method:		avated trial pit	Site	00 Baddaala Baad Otairaanaa		ate	15.02.21
	using a 3 ton tracked exca			28 Paddock Road, Staincross	_	cale	1:25
	Sample Date	nilo	Client	Andrew Bailey Architects	Log	ged By	ATS
Туре	Sample Deta Depth	Vane				Level	
Type	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legend
	10 110111 (111)				- op ()	(
ES	0.20						
HV	0.30	52,56, 50					
	[cally stiff pale yellow mottled light grey silty			
	[avelly CLAY. Gravel is subangular to rounded			
D	0.60		fine to c	coarse of lithorelict mudstone and ironstone.			
	ļ.						
	ļ-				0.85		
					0.03		0 -
	†						0 0
	ļ ,			ey locally light brown clayey silty subangular coarse GRAVEL of mudstone and siltstone,			\sim \circ
	[ow cobble content. Cobbles are subangular to			\circ
	<u> </u>			nded fine to coarse of lithrelict mudstone and			\circ
				ne (Probable Bedrock).			0 0
				,	1.70		0
				Trial pit complete at 1.70m	1.70		
	†			mar pic complete at m cm			
	į į						
	[
,	[
	<u> </u>						
	†						
	ļ.						
	•						
	†						
	 						
	†						
	ţ ,						
	[
	ļ						
	ļ [!]						
	}						
	[
	†						
	[
· ·	ļ						
	ļ.						
	ļ						
	†						
Remarks			•	Sample Types			
Sides stab	ole during excu			D - Disturbed W - Water		-	
Slow ????	? Of water int	to pit at 1.70-N	o rise	B - Bulk ES - Environmental		GE	VA
	sions 1.95mx0					CONSULT	ING
Hand vane	es below 0.40	m too friable					

		Tria	al Pit	Record			No No	16
							ract No	C398
Method:	Machine exc		Site			D	ate	15.02.21
	using a 3 ton tracked exca			28 Paddoc	k Road, Staincross	S	cale	1:25
			Client	Andrew	Bailey Architects	Log	ged By	ATS
Tura	Sample Deta	ails Vane		Andrew	Balley Architects		Level	
Type	Depth To-from (m)	kN/m²		Desc	ription	Depth (m)	(mAOD)	Legend
	()				w mottled light grey silty		(:::::::::)	
ES	0.20		gravelly	CLAY. Gravel is s	subangular to rounded fine			
			to coars	se of lithorelict muc	Istone and ironstone.	0.30		
D	0.50		Black C	OAL recovered as	very clayey subangular			
				nedium gravel.	, , , , ,			
		75 70 70				0.70		
HV	0.80	75,78,70						
	Ì				gravelly CLAY. Gravel is			
	Ţ		subang	ular fine to coarse	of lithorelict mudstone.			
						1.20		
					thinly to thickly laminated			
					as sandy subangular fine to			
			coarse	gravel. Sand is fine		1.55		
				Trial pit com	plete at 1.55m			
	1							
	Ţ							
	Ī							
	[
	-							
	-							
	[
	+							
	t							
	Ī							
	ł							
	 							
	İ							
	[
	}							
	}							
	<u> </u>							
	[
Remarks	da do 1			Sample Types	\A/_\A/_/			
	ole during excu Iwater encoun			D - Disturbed B - Bulk	W - Water ES - Environmental		C	M
	sions 2.10mx0			D - Duik	LO - LIIVIIUIIIIEIIIAI		U 8	V
	ed upon comp						CONSULT	ING
	·							

		Tria	Record		No	17 C398	
Method:	Machine exc	avated trial pi	t Site			ate	15.02.21
	using a 3 ton tracked exca	ne rated		28 Paddock Road, Staincross	So	cale	1:25
			Client	Andrew Bailey Architects	Logg	ged By	ATS
Туре	Sample Deta Depth	Vane		Description	Level Depth (m) (mAOD)		
	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legend
ES HV	0.20 0.30	62,80,70	gravelly	ally stiff pale yellow mottled light grey silty CLAY. Gravel is subangular to rounded fine			
D HV	0.80 0.80	72,84,80	to coarse	e of lithorelict mudstone and ironstone.	1.00		
			DAL recovered as very clayey subangular edium gravel.				
			Extreme	ly weak interbedded MUDSTONE with	1.30		
			subangu	Recovered as locally slightly clayey sandy lar fine to coarse gravel with a low cobble			
			content.	Cobbles are subangular to subrounded. Trial pit complete at 1.70m	1.70		
No ground Pit dimens	ble during excolor dwater encour sions 2.10x40o ed upon comp	itered m	[Sample Types D - Disturbed W - Water B - Bulk ES - Environmental		GA	M

		Tria	al Pit	Record		P No	18 C398
Method:	Machine exc	avated trial pi	t Site			ate	15.02.21
oui	using a 3 ton tracked exca	ne rated		28 Paddock Road, Staincross		cale	1:25
			Client	Andrew Bailey Architects	Log	ged By	ATS
Туре	Sample Deta Depth	ails Vane				Level	
. , , , ,	To-from (m)	kN/m²		Description	Depth (m)	(mAOD)	Legend
ES ES	0.20		a high co	GROUND: Dark grey very gravelly CLAY volbble content. Gravel is subangular fine to five sandstone and brick. Cobbles are lar of sandstone and brick.	vith D		
<u> </u>	0.60				0.90		
D	1.20						
HV	1.40	68,62,74	locally gr Gravel is sandstor	ck grey mottled light brown slightly gravell ravelly silty CLAY with a low cobble contest subangular fine to coarse of mudstone and cobbles are subangular to subrounde and ironstone.	nt. and		
					2.00		
				Trial pit complete at 2.00m	2.00		
No ground Pit dimens	table from 0-0 lwater encour sions 2.50m-0 ed upon comp	itered .40m	I	Sample Types D - Disturbed W - Water B - Bulk ES - Environmental		GS	M

Client: G & M Consulting Ltd	Site: Land at 28. Paddock Road Staincross, Barnsley. S75 6LG
Date:	METHOD
05/01/2021	Rotary air mist

Cape Site Services Ltd Unit 2, Rear of castle buildings, Carlton Road, Barnsley, South Yorkshire, S71 3HX



BH no	FROM	Meters TO	THICKNESS	Description			
1			THEREE	Description			
-	0.0	0.5	0.5	Fill			
	0.5	1.5	1.0	Clay yellow brown sandy			
	1.5	5.0	3.5	Sandstone grey brown silty with odd mudstone bands			
	5.0	7.8	2.8	Mudstone grey silty			
	7.8	10.5	2.7	Mudstone black			
	10.5	11.0	0.5	Coal dirty			
	11.0	11.5	0.5	Mudstone light grey silty			
	11.5	21.5	10.5	Sandstone grey silty mudstone bands			
	21.5	22.4	0.9	Coal			
	22.4	30.0	7.6	Mudstone grey silty			
	LL.1	50.0	7.0	Widdstolle giey slity			
				No gases recorded Water strike around 20.0m			
				water strike around 20.0m			
2							
	0.0	0.7	0.7	Clay yellow brown			
	0.7	2.5	1.8	Mudstone grey brown silty			
	2.5	3.0	0.5	Coal			
	3.0	3.5	0.5	Mudstone light grey silty			
	3.5	7.0	3.5				
	7.0	13.6	6.6	Sandstone grey brown with mudstone bands			
	13.6	14.4	0.8	Mudstone grey silty with odd sandstone bands			
	14.4	20.0	5.6	Coal			
-	14.4	20.0	3.0	Mudstone grey silty			
-				No cores recorded Water with 1200			
				No gases recorded Water strike around 12.0m			
3							
	0.0	0.8	0.8	Clay yellow grey			
	0.8	4.9	4.1	Mudstone grey silty			
	4.9	5.4	0.5	Coal dirty			
	5.4	6.0	0.6	Mudstone light grey silty			
		16.3	10.3	Sandstone grey silty with mudstone bands			
		17.1	0.8	Coal			
		20.0	2.9	Mudstone grey silty odd sandstone band			
			1	and and and additione pand.			
				No gases recorded Water strike around 18.0m			
				The gaste received Water strike around 16.000			

Driller	Driller's Assistant
I Wiles	R Hawkins & S Fish
Driller's Signature	Page1 of3

Client:	Site: Land at 28. Paddock Road		
G & M Consulting Ltd	Staincross, Barnsley. S75 6LG		
Date: 05/01/2021	METHOD Rotary air mist		

Cape Site Services Ltd
Unit 2, Rear of castle buildings,
Carlton Road, Barnsley,
South Yorkshire, S71 3HX



Measurer	nents In I			
BH no	FROM	TO	THICKNESS	Description
4				
	0.0	2.2	2.2	Clay yellow brown sandy
	2.2	3.8	1.6	Mudstone grey brown silty with sandstone bands
	3.8	4.7	0.9	Sandstone grey silty
	4.7	8.0	3.3	Mudstone grey silty
	8.0	8.1	0.1	Mudstone black
	8.1	17.5	9.4	Mudstone grey silty odd sandstone band
	17.5	18.5	1.0	Coal
	18.5	19.5	1.0	Mudstone grey silty
	19.5	30.0	10.5	Sandstone grey silty mudstone bands
				No gases recorded Water strike around 6.0m
5				
	0.0	0.7	0.7	Clay yellow grey
	0.7	3.0	2.3	Mudstone grey brown silty
	3.0	6.3	3.3	Mudstone grey silty
	6.3	6.7	0.4	Coal
	6.7	8.5	1.8	Mudstone light grey silty
	8.5	17.0	8.5	Sandstone grey brown silty with mudstone bands
	17.0	17.8	0.8	Coal dirty
	17.8	21.0	3.2	Mudstone grey silty
				No gases recorded Water strike around 15.0m
6				
	0.0	0.6	0.6	Clay yellow brown grey
	0.6	2.0	1.4	Mudstone grey brown
	2.0	3.2	1.2	Mudstone grey silty
	3.2	3.7	0.5	Coal dirty
	3.7	5.2	1.5	Mudstone light grey silty
	5.2	13.8	8.6	Sandstone grey brown silty with mudstone bands
	13.8	14.7	0.9	Coal dirty
	14.7	21.0	6.3	Mudstone grey silty
				No gases recorded Water strike around 12.0m

Driller's Assistant
R Hawkins & S Fish
Page2 of3

Client: G & M Consulting Ltd	Site: Land at 28. Paddock Road Staincross, Barnsley. S75 6LG	Cape Site Services Ltd	П
Date: 05/01/2021	METHOD Rotary air mist & Water flush	Unit 2, Rear of castle buildings, Carlton Road, Barnsley, South Yorkshire, S71 3HX	

BH no	nents In I		THOMATEC	
	FROM	TO	THICKNESS	Description
7				
	0.0	0.7	0.7	Clay yellow grey
	0.7	2.6	1.9	Mudstone grey brown silty
	2.6	3.1	0.5	Coal
	3.1	3.6	0.5	Mudstone light grey silty
	3.6	13.7	10.1	Mudstone grey brown silty with sandstone bands
	13.7	14.6	0.9	Coal dirty
	14.6	21.0	6.4	Mudstone grey silty
				No gases recorded Water strike around 12.0m
				Water flushed
3				water Hushed
	0.0	2.4	2.4	Clay yellow grey
-	2.4	2.9	0.5	Coal dirty
	2.9	5.0	2.1	Mudstone grey brown silty
	5.0	13.1	8.1	Sandstone grey brown with mudstone bands
	13.1	14.1	1.0	Coal dirty
	14.1	25.5	11.4	Mudstone grey silty odd sandstone band
	25.5	26.3	0.8	Coal dirty
	26.3	30.0	3.7	Mudstone grey silty
				get y and y
				No gases recorded
	_ =			
	== 14			
	1			
	-			
	-			

Driller	Driller's Assistant
I Wiles	R Hawkins & S Fish
Driller's Signature	Page3 of3
July 1	

.



APPENDIX CCOAL AUTHORITY PERMIT



Permit to Enter or Disturb Coal Authority Interests

Permit 21058

Name and Address of Permit Holder:

RMH Properties Ltd 18 Low Cudworth Green Cudworth Barnsley S72 8EF

Site Location:

Land at 28 Paddock Road Staincross Barnsley S75 6LG

This certificate hereby grants the above named Permit Holder a Permit to carry out:-

A Ground Investigation comprising ten boreholes to 30m to determine presence of shallow coal seams within the Authority's interests at the identified site location above as shown on the Grant Permit Boundary (overleaf) for the period of 12 months from the granted date shown below. The granting of this Permit does not constitute advice given by the Authority in relation to the proposed operations. It is the Permit Holder's responsibility to obtain appropriate health, safety, environmental, technical and legal advice.

Conditions:

- Air mist only to be used at 50m or further from receptors
- Water flush
- Gas Monitoring CO, CH4, CO2, O2, H2S at borehole and rig
- Operators undertaking the work must be in possession of this certificate and the Permit boundary plan at the time of works
- Appropriate borehole sealing without delay and to withstand site level changes

Signed:	Michael Amirtash	Granted Date:	1st December 2020
For and o	n behalf of The Coal Authority		
Nominate	d Representative: Michael Amirtash	, Permitting Manage	er;

The Coal Authority, Permitting Office, 200 Lichfield Lane, Mansfield, Notts, NG18 4RG

Tel: 01623 637450; E-Mail: permissions@coal.gov.uk



Granted Permit Boundary

Permit Ref: 21058

Permit Boundary:



These maps are reproduced from Ordnance Survey material with the permission of Ordnance Survey on behalf of the controller of Her Majesty's Stationary Office. © Crown Copyright. Unauthorised reproduction infringes Crown copyright and may lead to prosecution or civil proceedings. The Coal Authority. Licence No: 100020315. [216]



APPENDIX DPHOTOGRAPHIC RECORD



Figure 1 - Site Strip 1 looking east to west



Figure 2 - Site Strip 1 looking north



Figure 3 - Site Strip 2 looking east to west



Figure 4 - Site Strip 2 looking north-east