



Do Not Scale

Drawing Notes

Drawing & schedule based on the following information:
Architect's drawing/model: **VWYM2-PHS-XX-XX-DR-A-07000**
Revision: **P13**
Received: **20.07.2026**
Topographic Survey: **ZS Surveys - 4830**
Received: **15.05.2026**

Health, Safety & Environmental Notes

Depicts Low Residual Risk

Depicts Medium Residual Risk

Depicts High Residual Risk

Refer to Designer's Risk Assessment for Control Measures

General Notes
1. This drawing is to be read in accordance with all other relevant Adept drawings, third party drawings, specifications and other supporting documentation.
2. All given dimensions are as follows:
A. Level, coordinates and chainages in meters.
B. Pipe diameter, trench widths and Manhole details in millimeters.
3. All works adhere to all relevant CDM Regulations, project related CDM Documentation and health & safety Risk Assessments.

Key
S278 Boundary
Tactile Crossing
Illuminated 'Keep Left' Bollard
(See Adopt Dwg. No. 08.26003-ACE-00-ZZ-DR-C-2280 for detail)

Design Notes

1. All proposed road markings to be in accordance with the following:

- Traffic Signs Manual Chapter 5 2019 (TSM 5)
- Traffic Signs & Regulations & General Directions 2016 (TSRGD)

2. Road Markings diagram numbers referred to are those within TSRGD

3. The following design parameters have been used:

- Design Speed: 40 MPH or less

4. Road marking colours as indicated in the key. Materials and sisk resistance to be in accordance with BMDC specification

5. Road Markings to be set 150-300mm from traffic islands.

6. Existing lining to be removed by hydro-blasting. Any surfacing damaged as a result of the lining removal, which is not already within the surfacing extents, will necessitate a 15m surfacing patch.

7. All posts to be galvanized and powder coated

All road markings to be in accordance with notes and table below:

ROAD MARKINGS				
TSM REF	WIDTH (mm)	MARK (mm)	GAP (mm)	COLOUR
1003A	200	600	300	WHITE
1004	100	4000	2000	WHITE
1009A	100	600	300	WHITE
1023A	1250	3750	N/A	WHITE

1038** Arrow
A - Ahead Only
R - Right Only
L - Left Only
4000 Height: WHITE

1039** Arrow - Traffic Divide
R - Right Divide
8000 Height: WHITE

1040 Road Centre Line Hatching
Lines: 4000 Mark; 2000 Gap; 100 Wide; WHITE
Hatch: Continuous Mark; 150 Wide, 3000 Spacing, Angled 45° to Traffic Direction; WHITE

23.09.26 Initial issue

BHB

RP

P1

Date

Description

By

Chk

Rev

ADEPT

CIVIL AND STRUCTURAL CONSULTING ENGINEERS

Web: www.adeptcsce.com Email: info@adeptcsce.com Tel: 0113 239 4518

Office Address: 2312 Mill, Sunny Bank Mills, Town Street, Farnley, LS28 5UJ

Project

Wakefield Road, Mapplewell - Phase 2

Title

Section 278 - Road Marking Layout

Client

Vistry

Scale @ A0: 1:250

Initial author: BHB

Initial checker: RP

Approver: RP

Initial Date: SEP 26

Status: S2

Purpose: Preliminary

Adopt Project Number: 08.26003

Project Originator/Author/Revision Number: 08.26003-ACE-00-ZZ-DR-C-2250

P1